

DVE™ Viscometer

Our most affordable digital viscometer

What's Included

- Instrument
 - 6 spindles (RV/HA/HB) or 4 spindles (LV)
 - Carrying Case
 - Lab Stand (Model G)
 - Spindle Guard Leg*
- *Not applicable to HA / HB torque models

Optional Accessories

- Small Sample Adapter
- UL Adapter
- Thermosel
- DIN Adapter
- Viscosity Standards
- RV/HA/HB-1 Spindle
- Quick Action Lab Stand
- Temperature Bath
- Quick Connect/Extension Links



Features

User-friendly Interface

- Keypad control
- Sharp viewing screen for close up or distance viewing

No Calculations Required

Direct reading of viscosity

Displayed Info:

- Viscosity (cP, P, mPa•s or Pa•s)
- % Torque
- Speed/Spindle

Easy-to-Use

Range:

Push for determining full scale range (FSR) viscosity

Bubble Level:

Conveniently located for easy adjustment

Accuracy: ±1.0% of range

Repeatability: ±0.2%

18 Speeds

For complete range capability

| Model | VISCOSITY RANGE cP(mPa•s) | | SPEEDS (200 Available) | |
|-------|------------------------------|------|---------------------------|----------------------|
| | Min | Max | RPM | Number of Increments |
| DVELV | 1† | 2M | .3-100 | 18 |
| DVERV | 100†† | 13M | .3-100 | 18 |
| DVEHA | 200†† | 26M | .3-100 | 18 |
| DVEHB | 800†† | 104M | .3-100 | 18 |

† 1 cP achieved with UL Adapter accessory.
 15 cP on LV with standard spindles.

†† Minimum viscosity is achieved with optional RV/HA/HB-1 spindle.

M = 1 million cP = Centipoise
 mPa•s = Millipascal•seconds

